

SAFETY DATA SHEET

The Ruscoe Company

Page 1
Date Prepared: 06/01/2017
Date Printed: 06/06/17
MSDS Reference No.: R-202

1. Identification

Material Identity

Product Name: Ruscoe 12-1 LV (W2-1 LV)

Product Number: 56029Y

Generic ID: Nitrile Rubber Sealant

Company

The Ruscoe Company
485 Kenmore Blvd.
Akron, Ohio 44301
Telephone: 330-253-8148

Emergency Telephone: 800-424-9300
(Chemtrec – 24 hours/day)

Fax: 330-253-2933

2. Hazards identification

Classification of the substance or mixture

Flammable liquids	Category 2
Serious eye damage/ eye irritation	Category 2A
Acute toxicity; inhalation	Category 4
Specific target organ toxicity – single exposure respiratory system, central nervous system	Category 3
Skin corrosion/irritation	Category 2
Carcinogenicity: inhalation	Category 2
Specific target organ toxicity- single exposure respiratory tract irritation	Category 3
Specific target organ toxicity – repeated exposure inhalation(ears)	Category 2
Aspiration hazard	Category 1

GHS classification scale (1=severe hazard; 4=slight hazard)

Label elements

GHS label elements

The mixture is classified and labeled according to the the Globally Harmonized System (GHS).

Hazard pictograms



SAFETY DATA SHEET

The Ruscoe Company

Page 2

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

Signal Word: Danger

Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H332 Harmful if inhaled

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces.- No smoking

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

Response

P370+P378 In case of fire; use water spray, carbon dioxide, dry chemical or alcohol foam for extinction.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical attention.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/International regulations.

SAFETY DATA SHEET

The Ruscoe Company

Page 3
Date Prepared: 06/01/2017
Date Printed: 06/06/17
MSDS Reference No.: R-202

3. Composition/information on ingredients

Ingredients	CAS Number	% (by weight)
Methyl acetate	79-20-9	29-34
Synthetic rubber	9003-18-3	18-22
Acetone	67-64-1	10-13
Phenolic Resin	N/A	13-16
t-Butyl acetate	540-88-5	4-6
Ground limestone	1317-65-3	5-7
Magnesium silicate	14807-96-6	1-3
Aluminum powder	7429-90-5	2-4
Mineral spirits	8052-41-3	1.4 1-8
Xylenes, mixed isomers	1330-20-7	0.8-1.0
Hydrated amorphous silica	7631-86-9	0.4-0.8
Ethylbenzene	100-41-4	0.1-0.3
Polymeric phenolic antioxidant	68610-51-5	0.1-0.3
Formaldehyde	50-00-0	>10 ppb

VOC Content 75 g/l (3.1%)

4. First aid measures

Description of first aid measures

Inhalation: Remove to fresh air and keep at rest in apposition comfortable for breathing. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs give artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position Maintain an open airway. Loosen tight clothing such as a collar, tie belt or waistband.

Skin contact: Remove contaminated clothing as needed. Wash with plenty of soap and water. Immediately flush plenty of water for at least 15 minutes. Wash contaminated clothing before reuse..Seek medical attention if ill effect or irritation develops.

Eye contact: Immediately flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If easy to do remove contact lenses. If irritation persists seek medical attention.

Ingestion: Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

The Ruscoe Company

Page 4

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

May irritate and cause redness and pain. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Water spray, carbon dioxide, dry chemical, alcohol foamr.

For safety reasons unsuitable extinguishing agents: Solid water stream – may spread fire.

Special hazards arising from the substance or mixture: Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Runoff to sewer may create fire or explosion hazard. Water contaminated with this material be contained and prevented from being discharged to any waterway, sewer or drain.

Advice for firefighters

Hazardous thermal decomposition products: Carbon dioxide, carbon monoxide.

Protective equipment: Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Immediately evacuate personnel to safe areas. Keep people away and upwind of spill/leak. Remove all sources of ignition.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

Methods and material for containment or cleaning up:

Absorb with liquid-binding material (ie. Sand, diatomite, dry earth, acid binders, or other non-combustible material).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fire:

SAFETY DATA SHEET

The Ruscoe Company

Page 5

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

Keep ignition sources away – Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Specific end use(s) No further relevant information available.

8. Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters

Components with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

TWA 200 ppm - ACGIH

STEL 250 ppm - ACGIH

PEL 200 ppm - OSHA

67-64-1 acetone

TWA 500 ppm - ACGIH

STEL 750 ppm - ACGIH

REL 250 ppm - NIOSH

PEL 1000 ppm – OSHA

TWA 750 ppm – OSHA

STEL 1000 ppm – OSHA

540-88-5 t-butyl acetate

TWA 200 ppm - ACGIH

IDLH 1500 ppm – NIOSH Remarks: 10% LEL

TWA 200 ppm – OSHA

STEL 1000 ppm – OSHA

8052-41-3 mineral spirits

REL 350 mg/m³ – NIOSH TWA

CEIL 1800 mg/m³ – NIOSH 15 minute

TWA 500 ppm – OSHA

1330-20-7 xylenes mixed isomers

TWA 100 ppm – ACGIH

STEL 150 ppm – ACGIH 15 minute

TWA 100 ppm – OSHA

100-41-4 ethylbenzene

TWA 20 ppm – ACGIH

SAFETY DATA SHEET

The Ruscoe Company

Page 6
Date Prepared: 06/01/2017
Date Printed: 06/06/17
MSDS Reference No.: R-202

TWA 100 ppm - OSHA

50-00-0 Formaldehyde

STEL 2 ppm

TWA 0.75 ppm

Ingredients with biological limit values: None known.

Additional Information: Not available..

Exposure controls

Engineering measures: Good general ventilation (typically 10 air changes/hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select the glove material based on penetration times, rates of diffusion and degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection: Wear safety glasses with side shields or tightly sealed goggles. Wear a respirator if needed.

9. Physical and chemical properties

General information

Appearance:

Form:

Liquid

Color:

Silver colored

Odor:

Pleasant to pungent ketone

Odor threshold:

Not Determined

pH-value

7

Change in condition

Melting point/Melting range:

-99 to -94 °C (-106 to -97 °F)

SAFETY DATA SHEET

The Ruscoe Company

Page 7

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

Boiling point/Boiling range:	55 -58°C (131 to 136°F)
Flash point:	-13 to -1°C (9 - 30°F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	465°C (869 °F)
Decomposition temperature:	Not determined
Auto igniting:	Not determined
Danger of explosion:	No data available
Explosion Limits:	
Lower:	1.3 Vol %
Upper:	12 Vol %
Vapor Pressure @ 20 °C (68 °F)	241 hPa (181 mm Hg)
Density @ 20 °C (68 °F)	1.03 g/cm ³ (8.55 lbs/gal)
Relative density	Not determined
Vapor density	Not determined
Evaporation rate	Not determined
Solubility in/ Miscibility with water:	Not miscible or difficult to mix
Partition coefficient (n-octanol/water):	Not determined
Viscosity:	
Dynamic:	Not determined
Kinematic:	Not determined
Organic solvents:	50-51
VOC content	75 g/l (3.1 %)
Other information	No further relevant information available.

10. Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability

Thermal decomposition/conditions to be avoided: No decomposition under normal use conditions.

Possibility of hazardous reactions No dangerous reactions known expected.

Conditions to avoid Heat, sparks and flames. .

Incompatible materials: Acids, alkalies, nitrates, amines, ammonia, reducing agents and strong oxidizing agents.

Hazardous decomposition products: Carbon dioxide, carbon monoxide.

11. Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

79-20-9 methyl acetate

Oral LD50 6482 mg/kg (rat) (highest dose tested)

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

540-88-5 t-butyl acetate

SAFETY DATA SHEET

The Ruscoe Company

Page 8

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

Oral LD50 4500 mg/kg

1330-20-7 xylenes, mixed isomers

Oral LD50 4300 mg/kg

Primary irritant effect:

On the skin: Mild irritant effect.

On the eye: May cause moderate eye irritation.

Sensitization: No sensitizing effects known.

Additional toxicological information:

Carcinogenic categories

ACGIH Carcinogens

100-41-4 Ethylbenzene

A3 Confirmed animal carcinogen with unknown relevance to humans.

50-00-0 Formaldehyde

A2 Suspected human carcinogen.

1330-20-7 Xylene

A4 Not classifiable as a human carcinogen.

IARC (International Agency for Research on Cancer)

100-41-4 Ethylbenzene

2B Possibly carcinogenic to humans.

50-00-0 Formaldehyde

1 Carcinogenic to humans.

1330-20-7 Xylene

3 Not classifiable as to carcinogenicity to humans.

NTP (National Toxicology Program)

50-00-0 Formaldehyde

Known to be a human carcinogen.

US OSHA Specificall Regulated Substances: Potential cancer hazard

50-00-0 Formaldehyde

Potential cancer hazard.

12. Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No futher relevant information available.

13. Disposal considerations

Waste treatment methods

Recommendation:

Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Comply with applicable federal, state, and local regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SAFETY DATA SHEET

The Ruscoe Company

Page 9
Date Prepared: 06/01/2017
Date Printed: 06/06/17
MSDS Reference No.: R-202

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14. Transport information

UN-Number
DOT, ADR, IMDG, IATA UN1133
UN proper shipping name
DOT Adhesives, containing a flammable liquid.
ADR Not determined
IMDG, IATA Not determined
Transport hazard class(es)
DOT



Class 3 Flammable liquids.
Label 3
ADR Not determined
Class Not determined
IMDG< IATA Not determined
Class Not determined
Label Not determined
Packing group
DOT, ADR, IMDG, IATA II
Environmental hazards:
Marine pollutant: No
Special precautions for user Warning: Flammable liquids
Danger code (Kemler) 33
EMS Number: Not applicable.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT
Remarks: ERG Guide Number: 128
UN "Model Regulation": UN1133, Adhesives, 3, II

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

The Ruscoe Company

Page 10

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

Sara

Section 355 (extremely hazardous substances):

Mixture substances are not listed.

Section 313 (Specific toxic chemical listings):

Mixture substances are not listed.

TSCA (Toxic Substance Control Act):

1330-20-7 xylenes, mixed isomers is listed.

Proposition 65

Chemicals known to cause cancer:

Mixture substances are not listed or below amounts requiring listing.

Chemicals known to cause reproductive toxicity for females:

Mixture substances are not listed or below amounts requiring listing.

Chemicals known to cause reproductive harm to males:

Mixture substances are not listed.

Chemicals known to cause developmental toxicity:

Mixture substances are not listed or below amounts requiring listing..

TLV (Theshold Limit Value established by ACGIH)

Not determined.

NIOSH-Ca (National Institute for Occupational Safety and Health)

Mixture substances are not listed.

OSHA-Ca (Occupational Safety & Health Administration)

Mixture substances are not listed.

GHS label elements

The mixture is classified and labeled according to the Globally Harmonized System (GHS)

Chemical safety assesment: A chemical Safety Assesment has not been carried out.

16. Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of the need that the information is current, applicable, and suitable to their circumstances.

Date of preparation/last revision 2/22/2017 – 5/19/2017 - 6/1/2017

Abbreviations and acronyms:

ADR: Accord European sur le transport des marchandises par Route (European Agreement concerning the international Carriage of Dangerous Goods)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Government Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

SAFETY DATA SHEET

The Ruscoe Company

Page 11

Date Prepared: 06/01/2017

Date Printed: 06/06/17

MSDS Reference No.: R-202

LC50: Lethal concentration, 50 percent

LD50: Lethal Dose, 50 percent

End of SDS