



BOSS[®] 393 Gutter-Seal

TYPICAL PROPERTIES

Uncured

Tack-Free Time	15 min.
Cure Time at 75°F (24°C) and 50% RH (3/8" thickness)	24 hours
Extrusion Rate	400 g/min.

Cured – Physical

Elongation	300%
Durometer Hardness, Shore A, points	26
Tensile Strength, psi	250
Service Temperature	-40°F - 325°F
Application Temperature	-35°F - 140°F

*Primers may be required for certain substrates

*Information on this data sheet is subject to change without notice and should not be used for writing specifications.

For additional information on specific applications, contact Accumetric, LLC



DESCRIPTION

BOSS[®] 393 Gutter-Seal is a new VOC compliant sealant in all 50 states. **BOSS[®] 393 Gutter-Seal** was designed without the harsh smells of solvents, it's non-flammable, with no shrinking. **BOSS[®] 393 Gutter-Seal** is fast curing and provides permanent elastic adhesion to most surfaces.

BOSS[®] 393 Gutter-Seal is recommended for sealing all types of gutters, downspouts, ducts and ventilators. **BOSS[®] 393 Gutter-Seal** is excellent for sealing seams, joints and cracks in gutter troughs, HVAC ducts and sheet metal. **BOSS[®] 393 Gutter-Seal** cures on exposure to atmospheric moisture to form a durable flexible watertight seal. **BOSS[®] 393 Gutter-Seal** can be applied and tooled in most weather conditions (-35° F to +140°F), maintains adhesion and will not crack.

FEATURES

- VOC Compliant in all 50 states
- No lasting odors
- No shrinkage
- Non-flammable
- Fast curing
- Permanent elastic seal
- Long 4" nozzle for hard-to-reach areas
- Guns as low as -40°F
- All weather plastic cartridge

HOW TO USE

Applying the Material – Tack-Free Time

BOSS® 393 Gutter-Seal is supplied ready-to-use. Under pressure it flows readily from its container. The paste-like consistency makes it easy to work; a spatula or wooden paddle can be used for tooling the surface.

The cure progresses inward from the surface. At conditions of at least 75°F (24°C) and 50 percent relative humidity, the sealant forms a tack-free skin in 15-20 minutes. Tooling is not practical after this skin begins forming, and should be completed within 5-7 minutes of application, even though this may require alternate periods of applying and tooling. Likewise, if masking tape has been used to mark off an area, it should be removed before the tack-free skin forms.

CLEAN UP

Uncured sealant can be easily removed using a solvent such as alcohol or acetone. For an environmental and health friendlier choice use **BOSS® Biggie Wipes**. If the sealant is cured it must be removed mechanically by cutting and scraping.

COLORS

BOSS® 393 Gutter-Seal is available in clear, white and aluminum.

PACKAGING

BOSS® 393 Gutter-Seal is available in standard caulking cartridges.

SHIPPING LIMITATIONS

None.

Reactive VOC 16 g/L (<3% wt)

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 393 Gutter-Seal** has a shelf life of 12 months from date of shipment. In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. **IN CASE OF EYE CONTACT**, flush eyes with water for 15 minutes. Obtain medical attention. **IN CASE OF SKIN CONTACT**, remove from skin and flush with water. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Accumetric's control, we can accept no liability for the results obtained. Accumetric's sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Accumetric will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

MADE IN U.S.A.

BOSS® PRODUCTS

Accumetric, LLC®
350 Ring Road
Elizabethtown,
Kentucky 42701 USA
800-928-BOSS(2677)
TEL (270)769-3385
FAX (270)765-2412
Outside U.S.
TEL +1(270)769-3385
FAX +1(270)765-2412

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662)634-3060
FAX (662)634-3066

www.bossproducts.com