

Pro-Series®

- Formulated for sealing aluminum, galvanized and vinyl clad gutters and down spouts
- Will not crack

**Pro-Series GS-121 VOC Rubber Gutter & Seam Sealant** is a formulation containing SBR Rubber and high quality resins, which cures to a tough, rubbery stage that will expand and contract with the change of weather and will not crack. Formulated especially for sealing aluminum, galvanized, and vinyl clad gutters and downspouts.

**GS-121 VOC** is excellent for sealing seams, joints, and cracks in gutter troughs, and will bond to any clean surface. **GS-121 VOC** may also be used on sheet metal work, air conditioning, heating ducts, ventilators, etc. This product can be easily painted and will not lose its strong waterproof bond or become brittle even after years of exposure to freezing and thawing.



GS-121 RUBBER GUTTER & SEAM

GUTTER SEALANT

OSI®



**! DANGER!** EXTREMELY FLAMMABLE. VAPOURS MAY CAUSE FLARE-UP. IRRITANT. HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Carefully read back panel for other cautions.

**! PELIGRO!** EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEBEN CAUSAR COMBUSTION ESPONTANEA, DAÑO SI SE INHALA O SE INGERE. PUEDE CAUSAR IRRITACION A LOS OJOS, LA PIEL O EL TRACTO RESPIRATORIO. Lea cuidadosamente el panel posterior sobre otras precauciones.

10.2 fl oz (301 ml)

• Para sellar careceridos y bajantes de aluminio, galvanizado, vinyl clad gutters and downspouts  
• Excelente para el trabajo en laminas de metal, conductores y uniones de respiraderos  
• Expansible y contrae con los cambios de temperatura  
• Cures to a tough, rubbery stage

• For sealing aluminum, galvanized, vinyl clad gutters and downspouts  
• Excellent for sheet metal work, ducts, and ventilators  
• Expanses and contracts with temperature change  
• Cures to a tough, rubbery stage

GS-121 RUBBER GUTTER & SEAM

GUTTER SEALANT



OSI®

PHYSICAL PROPERTIES

Type	Synthetic rubber and resins
Solids by weight	10.2 oz. cartridge: 75%
Flammability	Extremely Flammable while drying
Toxicity	Toxic only if swallowed
Flash point	9° F. cartridge
Clean up	Mineral spirits or paint thinner (follow precautions and instructions for use on solvent label)

\*NOTE: Open time can vary due to prevailing environmental conditions present at time of application, such as temperature, humidity and wind velocity.

\*\*For fast, smooth, easy application during cold weather, sealant should be kept at room temperature 24 hours prior to use.

FEATURES

- Expands and contracts with temperature change with no loss of adhesion
- Air cures into a tough, rubbery gasket
- Always remains pliable

APPLICATION PROCEDURES

1. It is very important that all surfaces be clean and free of dust, dirt, oil, rust, water and ice.
2. Any 1/10 gallon caulking gun can be used with the GS-121 Rubber Gutter & Seam Sealant cartridge. Simply cut nozzle to size of bead and puncture seal.

PRECAUTIONS

Contains mineral spirits, methyl acetate and toluene. **DANGER! EXTREMELY FLAMMABLE.** Vapors may ignite explosively. Do not use or store near heat, sparks or open flame. Do not smoke when using this product. Extinguish all flames and pilot lights and turn off all sources of ignition, including stoves, heaters and electric motors, during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use in a well-ventilated area. Avoid breathing vapors. Avoid contact with eyes and skin. Prolonged or repeated exposure may affect the nervous system causing dizziness, headache or nausea. If you experience eye watering, headache or dizziness, leave the area to obtain fresh air. Do not take internally. **FIRST AID:** If swallowed do not induce vomiting, call a physician or Poison Control center immediately. For eye contact flush with water for 15 minutes, call a physician. For skin contact wash thoroughly with soap and water. If overcome by vapors, get fresh air. **KEEP OUT OF THE REACH OF CHILDREN.** If this product is used in an OSHA regulated workplace consult the MSDS available from your distributor before use. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver and kidney damage or may cause cardiac arrhythmia. INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

PACKAGING

GS-121 Rubber Gutter & Seam Sealant  
10.2 oz. Cartridges:  
12 per case with 3" spout  
White - IDH# 1117415  
Aluminum - IDH# 1117417

STORAGE

Store in a cool, dry area.

COVERAGE

1/4" bead size:  
approx. 34 lin. ft. per 10.2 oz. cartridge

FOR COMMERCIAL USE CONTACT HENKEL TECHNICAL DEPARTMENT

For more information contact  
Henkel Corporation Technical Services at phone:  
(800) 321-0253  
or visit [www.osisealants.com](http://www.osisealants.com)



Henkel Corporation  
Professional and Consumer Adhesives  
Avon, OH 44011